

The tapping machine can be used on both iron-based and non-iron-based materials, such as stainless, copper, aluminum, etc.

## Main Technical Parameters

Model	Size	No. of Spindle	Productivity (pcs/min.)		Main Motor (kw)	Motor of Material Mixing (kw)	Oil Pump (kw)	Air Pressure (kg/cm)	Dimension(L x W x H/mm)	Weight (kg)
			Flange	Hex						
RLDH-M8-4	M5	4	140	200	0.75-4	0.55	0.25	2-3	1450×1600×1800	1110
	M6	4	130	180						
	M8	4	120	160						
RLDH-M12-4	M10	4	100	140	1.5-4	0.55	0.25	3-4	1500×1900×1750	1160
	M12	4	90	120						
	M14	4	80	100						
RLDH-M18-4	M16	4	60	80	2.2-6	0.75	0.25	4-5	1700×2000×1800	1280
	M18	4	50	70						
RLDH-M24-4	M20	4	40	60	2.2-8	1.1	0.25	4-6	1750×2100×1850	1400
	M22	4	30	50						
	M24	4	25	40						
RLDH-M30-4	M27	4	20	32	3-8	1.1	0.25	4-7	1750×2100×1850	1400
	M30	4	16	28						

Workshop and machine stock:





