





□□□□□□ □□□□:

□□ □□□□ .□□□□□□□ □□□□□□ □□□□ □□ □□□□□□□□ □□□□□□ □□□ □□□□ □□□ □□□ □□□ □□□□□□□□ □□□□□□□ □□□□□□ □□□□□□ □□□□□□.

搓丝机参数

/ THREAD ROLLING MACHINE PARAMETERS

序号 Order	机型 Model	 外径 (mm) Diameter	 长度 (mm) Screw length	 牙长 (mm) Thread length	 牙板 Moving Dies Stationary Length	 马力 (HP) Main Motor	 产量 (PCS/MIN.) Max.output	 重量 (KG) Approx.wt	 机台尺寸 (mm) Machine Size
-------------	-------------	--	--	---	--	--	---	---	--

CY搓丝机

CY90°Feeding (GEAR IN OUTSIDE) 《CY系列可配合买方尺寸，更改90°牙板》

1	CY05Z	3-5	50/75	50	76/89/25	2.2	90-120	1000	1600×1300×1650
2	CY06Z	3-6	50/75	75	90/105/25	4	160-185	1500	1800×1500×1700
3	CY10Z	6-10	100/150/200/300	100	150/165/25	11	85-120	3670	2896×1216×2180
4	CY12Z	8-12	100/150/200/300	100	190/215/35	15	65-85	5600	3265×1524×2345
5	CY16Z	12-16	150/200/300	100	230/265/38	22	45-60	6700	3500×1900×2200
6	CY20Z	14-20	200/300	150	290/330/50	30	40-50	14000	2200×4700×2200
7	CY24Z	16-24	200/300	150	380/420/50	45	35-45	18130	5100×2320×2600
8	CY30Z	20-30	250/300	150	400/450/50	55	20-30	22330	5250×2650×2950
9	CY02X	1-3	25	20	51/64/19	0.75	275-325	830	1150×1000×1680
10	CY04X	2-4	38	32	76/89/25	1.5	230-280	1040	1560×1180×1790
11	CY06X	3-6	50/75	50	90/105/25	4	170-200	1900	2140×1180×2100
12	CY08X	4-8	75	50	108/127/25	5.5	180-200	2215	2410×1180×2100
13	CY10X	6-10	100/150	65	150/165/25	15	130-160	4530	3100×1640×1970
14	CY12X	8-12	100/150	75	190/215/35	22	100-140	5300	3300×1530×1982
15	CY16X	12-16	150	80	230/265/38	30	75-120	7600	3720×1800×2620
16	CY20X	14-20	150	80	290/330/50	37.5	73-85	14000	3024×1824×2300

□□□□□□ □□□□□□:



斜送送料方式

素材进料与中仁成30°

Transportation Material

Sloping filling-30 degree obliquity with main slider



直送送料方式

素材进料与中仁成90°

Transportation Material

Sloping filling-90 degree obliquity with main slider

□□□□□□ □□□□□□ □□□:



□□□□□ □□ □□□□:

