

Table 1: Specifications

The table lists the specifications for various models of the JXR series. The specifications include the number of stations, maximum diameter, die diameter, die length, die diameter, die length, stroke, speed, horsepower, weight, and dimensions.

Model	STATION	MAX. DIA. (mm)	DIA. (mm)	Die Length (mm)	Die Dia. (mm)	DIE LENGTH (mm)	STROKE (mm)	Speed (per.min)	Horsepower (HP)	Weight (T)	Dimensions (mm)
JXR08B-6S-12	6	8	8	M4-M5	12	38	40	175/350	10	3.5	195 × 135 × 130
JXR11B-6S-14	6	11	10	M5-M6	14	50	60	120/240	15	4.3	230 × 155 × 135
JXR11B-6SL-20	6	11	10	M5-M6	20	50	65	110/200	20	4.5	230 × 155 × 135
JXR11B-6SL-35	6	11	10	M5-M6	35	50	125	110	20	4.5	230 × 155 × 135
JXR14B-6S-18	6	15	14	M6-M8	18	60	70	75/160	20	8	300 × 195 × 175
JXR14B-6SL-30	6	15	14	M6-M8	30	60	100	85/160	30	8	300 × 198 × 175
JXR14B-6SL-50	6	15	14	M6-M8	50	60	160	85	30	8.5	300 × 198 × 175
JXR17B-6S-20	6	17	17	M8-M10	20	70	80	65/130	20	10	350 × 220 × 185
JXR17B-6SL-50	6	17	17	M8-M10	50	70	160	80	40	10.5	360 × 220 × 185
JXR17B-6SL-70	6	17	17	M8-M10	70	70	220	80	50	10.5	360 × 220 × 185
JXR19B-6S-25	6	20	19	M10-M12	25	80	95	95	40	10.5	360 × 220 × 185
JXR19B-6SL-50	6	20	19	M10-M12	50	80	160	75	50	16	380 × 245 × 196
JXR19B-6SL-70	6	20	19	M10-M12	70	80	220	65	60	16	380 × 235 × 196
JXR22B-6S-30	6	22	22	M12-M14	30	80	160	80	60	18	380 × 235 × 196
JXR22B-6SL-60	6	22	22	M12-M14	60	80	220	75	60	18	380 × 235 × 196
JXR24B-6S-35	6	24	24	M14-M16	35	100	160	75	75	27.5	550 × 248 × 270
JXR24B-6SL-70	6	24	24	M14-M16	70	100	210	65	75	27.5	550 × 248 × 270
JXR27B-6S-40	6	27	29	M16-M18	35	100	160	75	100	30	550 × 248 × 270
JXR27B-6S-70	6	27	29	M16-M18	70	100	210	65	150	30	550 × 248 × 270
JXR33B-6SL-40	6	33	30	M18-M20	35	140	160	70	150	45	650 × 300 × 280
JXR33B-6SL-80	6	33	30	M18-M20	80	140	280	60	200	50	650 × 300 × 280

Table 2: Specifications

