



SCREW MAKER

One die two blow heading machine. widely used to produce standard and non-standard screw. the machine is easy to operate and stable in performance



- Professional
- Good quality
- Energy conservation

20 YEARS

20 years of professional export

PRODUCT DISPLAY



PRODUCT PARAMETERS

Heading machine

Specification	RSH-5	RSH-10	RSH-15	RSH-20	RSH-20B	RSH-24	RSH-24B	RSH-25
Max.blank Dia.	3mm	4mm	5mm	6mm	6mm	8mm	8mm	10mm
Max.blank length	32mm	40mm	50mm	80mm	100mm	100mm	120mm	150mm
Main slide Stroke	48mm	62mm	81mm	124mm	136mm	140mm	170mm	220mm
Output(pcs/min)	135-160	160-180	140-160	100	80	80	80	60
Main Die Dia.	20mm	30mm	34.5mm	45mm	45mm	48mm	48mm	55mm
Cut off die Dia	13.5 mm	15mm	19mm	25mm	25mm	25mm	25mm	28mm
Punch die (1st)	18 mm	25 mm	31mm	36mm	36mm	38mm	38mm	38mm
Punch die (2nd)	18 mm	25mm	31mm	36mm	36mm	38mm	38mm	38mm
Main motor power	1.5kw	2.2kw	3kw	4kw	4kw	5.5kw	5.5kw	7.5kw
Dimensions LxWxH(mm)	1140x810 x900	1680x940 x1050	2100x1100 x1200	2800x1150 x1270	3050x1150 x1270	3800x1600 x1500	3270x1200 x1340	4450x1740 x1510



Ricet heading machine

Specification	RSH-5A	RSH-15A	RSH-20A
Max.blank Dia.	3mm	5mm	6mm
Max.blank length	22mm	70mm	70mm
Main slide Stroke	38mm	102mm	136mm
Output(pcs/min)	100-120	70-100	60-75
Main Die Dia.	20mm	34.5mm	45mm
Cut off die Dia	13.5 mm	19mm	25mm
Punch die (1st)	18 mm	31mm	36mm
Punch die (2nd)	18 mm	31mm	36mm
Main motor power	1.1kw	3kw	4kw
Dimensions LxWxH(mm)	1645x780x850	2400x950x1150	3020x1050x1215

OFFICE IN INDIA



STUTTGART EXHIBITION IN 2019



MUMBAI EXHIBITION IN 2019



WORKSHOP

