	RSH6-120
$\square\square\square\square\square\square\square\square\square\squaremm\square$	6
$\square\square\square\square\square\square\square\square\square\squaremm\square$	120
$\square\square\square\square\square\square\square\square\square\squaremm\square$	140
$\square\square\square$ mm \square	150
□□□PC/min□	70-80
$\square\square\square\square\square mm\square$	φ50x150
[][][][][][][][][][][][][][][][][][][]	φ35x120
$\square\square\square\square\square\square\square\square\square\squaremm\square$	φ35x120
$\square\square\square\square\square mm\square$	φ24x40
$\square\square\square\square\square\squaremm\square$	12x35x77
	7.5HP/5.5kW
$\square\square\square\square\squareL*W*H\square\square M\square$	2.80x1.40x1.60
	3600

Its purpose is to the selected such as carbon steel, stainless steel, aluminum, copper and other metal wire, with appropriate mould, according to the allowable pressure wire than, under the effect of crankshaft connecting rod drive the slider, automated, fast after the required size of the wire will be automatically shear, extrusion in the mould for needed fastener head type, stem diameter, facilitate thread rolling, or become a qualified rivet type fastener.



Professional

Good quality 🗹

Energy conservation



20 years of professional export



PRODUCTION AREA

Provide You With A Variety Of Products Meet The Different Needs Of Customers













