

規格表

本規格は、本規格に準拠する製品の仕様を示すものであり、本規格に準拠する製品の仕様を示すものではありません。

品名	STATION	MAX. 径 (mm)	CUT-OFF DIA. (mm)	径 (mm)	径 (mm)	DIE 径 (mm)	径 (mm)	OUTPUT (per.min)	HP	寸法	寸法 (cm)
JXR08B-6S-12	6	8	8	M4-M5	12	38	40	120/240	10	3.5	195×135×130
JXR11B-6S-14	6	11	10	M5-M6	14	50	60	120/240	15	4.3	230×155×135
JXR11B-6SL-20	6	11	10	M5-M6	20	50	65	120/240	20	4.5	230×155×135
JXR11B-6SL-35	6	11	10	M5-M6	35	50	125	110	20	4.5	230×155×135
JXR14B-6S-18	6	15	14	M6-M8	18	60	70	120/240	20	8	300×195×175
JXR14B-6SL-30	6	15	14	M6-M8	30	60	100	120/240	30	8	300×198×175
JXR14B-6SL-50	6	15	14	M6-M8	50	60	160	85	30	8.5	300×198×175
JXR17B-6S-20	6	17	17	M8-M10	20	70	80	120/240	20	10	350×220×185
JXR17B-6SL-50	6	17	17	M8-M10	50	70	160	80	40	10.5	360×220×185
JXR17B-6SL-70	6	17	17	M8-M10	70	70	220	80	50	10.5	360×220×185
JXR19B-6S-25	6	20	19	M10-M12	25	80	95	95	40	10.5	360×220×185
JXR19B-6SL-50	6	20	19	M10-M12	50	80	160	75	50	16	380×245×196
JXR19B-6SL-70	6	20	19	M10-M12	70	80	220	65	60	16	380×235×196
JXR22B-6S-30	6	22	22	M12-M14	30	80	160	80	60	18	380×235×196
JXR22B-6SL-60	6	22	22	M12-M14	60	80	220	75	60	18	380×235×196
JXR24B-6S-35	6	24	24	M14-M16	35	100	160	75	75	27.5	550×248×270
JXR24B-6SL-70	6	24	24	M14-M16	70	100	210	65	75	27.5	550×248×270
JXR27B-6S-40	6	27	29	M16-M18	35	100	160	75	100	30	550×248×270
JXR27B-6S-70	6	27	29	M16-M18	70	100	210	65	150	30	550×248×270
JXR33B-6SL-40	6	33	33	M18-M20	35	140	160	70	150	45	650×300×280
JXR33B-6SL-80	6	33	33	M18-M20	80	140	280	60	200	50	650×300×280

写真



