La máquina laminadora de roscas adopta un diseño de distancia de 1/2 tornillo escalonado de la placa laminadora de roscas de dos perfiles de rosca. Una placa es fija, la placa móvil está en la placa fija y realiza un movimiento en línea recta hacia adelante y hacia atrás, cuando la pieza de trabajo se alimenta entre dos placas, la placa móvil avance, gire la pieza de trabajo y haga que su superficie se deforme plásticamente en hilo. Para enrollar hilo en el vástago en blanco de un perno después de haberlo enfriado.

PRODUCT DISPLAY

Various types of thread rolling machine to meet your various needs

CY06Z

CY08Z

CY10Z

CY12Z

CY16Z

CY30Z

CY02X

CY05X

CY06XN

CY06X

CY08X

CY12X

THREAD ROLLING MACHINE PART OF THE STRUCTURE

TRANSPORTATION MATERIAL

Sloping filling-90 degree obliquity with main slider

TRANSPORTATION MATERIAL

Sloping filling-30 degree obliquity with main slider

NO HEAD SCREW

Through no head screw feeding system.the system solves problems in no head 'screw bottleneck with advanced value ir machinery.

ORBITAL BRACKET

To stabilize filling progress in order to avoid floating head and increases fine quality.

FORCIBLE OIL CARRYING

It replaces traditional acrylic oiler which damaged main slider. This precision filter system not only lowers direct cost in production but also extend life usage in recycle.

AUTO FEEDING SYSTEM

Replced cam by auto feed system, effectively avoids the cam abrasion in the production process.