


Descripción del producto:

Nuestra máquina de laminado de roscas se utiliza ampliamente en China doméstica y en el extranjero. Es con gran velocidad, y la operación fácil.

搓丝机参数

/ THREAD ROLLING MACHINE PARAMETERS

| 序号 Order | 机型 Model |  外径 (mm) Diameter |  长度 (mm) Screw length |  牙长 (mm) Thread length |  牙板 Moving Dies Stationary Length |  马力 (HP) Main Motor |  产量 (PCS/MIN.) Max.output |  重量 (KG) Approx.wt |  机台尺寸 (mm) Machine Size |
|-------------|-------------|--|--|---|--|--|---|---|--|
|-------------|-------------|--|--|---|--|--|---|---|--|

CY搓丝机

CY90°Feeding (GEAR IN OUTSIDE) 《CY系列可配合买方尺寸，更改90°牙板》

| | | | | | | | | | |
|----|-------|-------|-----------------|-----|------------|------|---------|-------|----------------|
| 1 | CY05Z | 3-5 | 50/75 | 50 | 76/89/25 | 2.2 | 90-120 | 1000 | 1600×1300×1650 |
| 2 | CY06Z | 3-6 | 50/75 | 75 | 90/105/25 | 4 | 160-185 | 1500 | 1800×1500×1700 |
| 3 | CY10Z | 6-10 | 100/150/200/300 | 100 | 150/165/25 | 11 | 85-120 | 3670 | 2896×1216×2180 |
| 4 | CY12Z | 8-12 | 100/150/200/300 | 100 | 190/215/35 | 15 | 65-85 | 5600 | 3265×1524×2345 |
| 5 | CY16Z | 12-16 | 150/200/300 | 100 | 230/265/38 | 22 | 45-60 | 6700 | 3500×1900×2200 |
| 6 | CY20Z | 14-20 | 200/300 | 150 | 290/330/50 | 30 | 40-50 | 14000 | 2200×4700×2200 |
| 7 | CY24Z | 16-24 | 200/300 | 150 | 380/420/50 | 45 | 35-45 | 18130 | 5100×2320×2600 |
| 8 | CY30Z | 20-30 | 250/300 | 150 | 400/450/50 | 55 | 20-30 | 22330 | 5250×2650×2950 |
| 9 | CY02X | 1-3 | 25 | 20 | 51/64/19 | 0.75 | 275-325 | 830 | 1150×1000×1680 |
| 10 | CY04X | 2-4 | 38 | 32 | 76/89/25 | 1.5 | 230-280 | 1040 | 1560×1180×1790 |
| 11 | CY06X | 3-6 | 50/75 | 50 | 90/105/25 | 4 | 170-200 | 1900 | 2140×1180×2100 |
| 12 | CY08X | 4-8 | 75 | 50 | 108/127/25 | 5.5 | 180-200 | 2215 | 2410×1180×2100 |
| 13 | CY10X | 6-10 | 100/150 | 65 | 150/165/25 | 15 | 130-160 | 4530 | 3100×1640×1970 |
| 14 | CY12X | 8-12 | 100/150 | 75 | 190/215/35 | 22 | 100-140 | 5300 | 3300×1530×1982 |
| 15 | CY16X | 12-16 | 150 | 80 | 230/265/38 | 30 | 75-120 | 7600 | 3720×1800×2620 |
| 16 | CY20X | 14-20 | 150 | 80 | 290/330/50 | 37.5 | 73-85 | 14000 | 3024×1824×2300 |

Alimentar manera:



斜送送料方式

素材进料与中仁成30°

Transportation Material

Sloping filling-30 degree obliquity with main slider



直送送料方式

素材进料与中仁成90°

Transportation Material

Sloping filling-90 degree obliquity with main slider

Máquina de embalaje:



Exposición en el Extranjero:

