

La máquina de rodadura de rosca adopta un diseño de distancia de rodillo de rosca de perfil de dos roscas 1/2 diseño de distancia de tornillo, una placa es fija, la placa móvil está en la placa fija, el movimiento de línea recta hacia adelante y hacia atrás, cuando la pieza de trabajo se alimenta entre dos placas, la placa móvil se mueve hacia adelante. Para rodar el rostro sobre el vástago en blanco de Bolt después de tener la cabeza fría.

RAINBOW

HIGH-SPEED AUTOMATIC THREAD ROLLING MACHINE



- Professional ✓
- Good quality ✓
- Energy conservation ✓

20 YEARS

20 years of professional export

PRODUCT DISPLAY

Various types of thread rolling machine to meet your various needs



CY06Z



CY08Z



CY10Z



CY12Z



CY16Z



CY30Z



CY02X



CY05X



CY06XN



CY06X



CY08X



CY12X

THREAD ROLLING MACHINE PART OF THE STRUCTURE



TRANSPORTATION MATERIAL

Sloping filling-90 degree obliquity with main slider



TRANSPORTATION MATERIAL

Sloping filling-30 degree obliquity with main slider



NO HEAD SCREW

Through no head screw feeding system, the system solves problems in no head 'screw bottleneck with advanced value Ir machinery.




ORBITAL BRACKET

To stabilize filling progress in order to avoid floating head and increase fine quality.



FORCIBLE OIL CARRYING

It replaces traditional acrylic oiler which damaged main slider. This precision filter system not only lowers direct cost in production but also extends life usage in recycle.



AUTO FEEDING SYSTEM

Replaced cam by auto feed system, effectively avoids the cam abrasion in the production process.