La machine à rouler les filets adopte une plaque de laminage de filetage à deux profils de filetage décalée à 1/2 distance de vis, une plaque est fixe, la plaque mobile est sur la plaque fixe pour effectuer un mouvement en ligne droite d'avant en arrière, lorsque la pièce à travailler passe entre deux plaques, plaque mobile avancer, tordre la pièce à travailler, transformer sa surface en plastique en filetage. Pour rouler le fil sur la tige vierge du boulon après avoir été embouti à froid.

PRODUCT DISPLAY

Various types of thread rolling machine to meet your various needs

CY06Z

CY08Z

CY10Z

CY12Z

CY16Z

CY30Z

CY02X

CY05X

CY06XN

CY06X

CY08X

CY12X

THREAD ROLLING MACHINE PART OF THE STRUCTURE

TRANSPORTATION MATERIAL

Sloping filling-90 degree obliquity with main slider

TRANSPORTATION MATERIAL

Sloping filling-30 degree obliquity with main slider

NO HEAD SCREW

Through no head screw feeding system.the system solves problems in no head 'screw bottleneck with advanced value ir machinery.

ORBITAL BRACKET

To stabilize filling progress in order to avoid floating head and increases fine quality.

FORCIBLE OIL CARRYING

It replaces traditional acrylic oiler which damaged main slider. This precision filter system not only lowers direct cost in production but also extend life usage in recycle.

AUTO FEEDING SYSTEM

Replced cam by auto feed system, effectively avoids the cam abrasion in the production process.