

La rullatrice adotta due piastre di rullatura con profilo filettato sfalsate a 1/2 distanza della vite, una piastra è fissa, la piastra mobile si trova sulla piastra fissa e fa un movimento in linea retta avanti e indietro, quando il pezzo da lavorare si alimenta tra due piastre, la piastra mobile si sposta in avanti, ruota il pezzo da lavorare, trasforma la sua deformazione plastica superficiale nella filettatura. Per rullare la filettatura sul gambo grezzo del bullone dopo averlo ricalcato a freddo.

RAINBOW

HIGH-SPEED AUTOMATIC THREAD ROLLING MACHINE



Professional ✓
Good quality ✓
Energy conservation ✓

20 YEARS

20 years of professional export

PRODUCT DISPLAY

Various types of thread rolling machine to
meet your various needs



CY06Z



CY08Z



CY10Z



CY12Z



CY16Z



CY30Z



CY02X



CY05X



CY06XN



CY06X



CY08X



CY12X

THREAD ROLLING MACHINE PART OF THE STRUCTURE



TRANSPORTATION MATERIAL

Sloping filling-90 degree obliquity with main slider



TRANSPORTATION MATERIAL

Sloping filling-30 degree obliquity with main slider



NO HEAD SCREW

Through no head screw feeding system, the system solves problems in no head 'screw bottleneck with advanced value in machinery.



ORBITAL BRACKET

To stabilize filling progress in order to avoid floating head and increase fine quality.



FORCIBLE OIL CARRYING

It replaces traditional acrylic oiler which damaged main slider. This precision filter system not only lowers direct cost in production but also extends life usage in recycle.



AUTO FEEDING SYSTEM

Replaced cam by auto feed system, effectively avoids the cam abrasion in the production process.