

La macchina per il rolling del filo adotta due piastre di rotolamento del filo del filo sfalsata 1/2 Design della distanza a vite, una piastra è fissa, la piastra mobile si trova sulla piastra fissa che fa il movimento della linea retta avanti e indietro, quando il pezzo di lavoro si nutre tra due piastre, la piastra mobile sposta il pezzo di rottura in avanti, rendere la sua deformazione in plastica di superficie nel filo. Per rotolare il filo su gambo bianco di bullone dopo essere stato a freddo.

RAINBOW

HIGH-SPEED AUTOMATIC THREAD ROLLING MACHINE



Professional ✓
Good quality ✓
Energy conservation ✓

20 YEARS

20 years of professional export

PRODUCT DISPLAY

Various types of thread rolling machine to
meet your various needs



CY06Z



CY08Z



CY10Z



CY12Z



CY16Z



CY30Z



CY02X



CY05X



CY06XN



CY06X



CY08X



CY12X

THREAD ROLLING MACHINE PART OF THE STRUCTURE



TRANSPORTATION MATERIAL

Sloping filling-90 degree obliquity
with main slider



TRANSPORTATION MATERIAL

Sloping filling-30 degree obliquity
with main slider



NO HEAD SCREW

Through no head screw feeding
system, the system solves problems
in no head 'screw bottleneck with
advanced value in machinery.



ORBITAL BRACKET

To stabilize filling progress in order
to avoid floating head and
increases fine quality.



FORCIBLE OIL CARRYING

It replaces traditional acrylic oiler
which damaged main slider. This
precision filter system not only
lowers direct cost in production
but also extends life usage in
recycle.



AUTO FEEDING SYSTEM

Replaced cam by auto feed system,
effectively avoids the cam abrasion
in the production process.