

Heading Machine

Model	RSH4-30G
Max. Blank Diameter (mm)	4
Max. Blank Length (mm)	30
Max. Cut off Length (mm)	48
Stroke (mm)	68
Output (Pcs/Min)	180-200
Main Die Diameter (mm)	Φ30X50
Punch Die Diameter (1st) (mm)	Φ25X65
Punch Die Diameter (2nd) (mm)	Φ25X65
Cut off Die Diameter (mm)	Φ15X30
Cutter Size (mm)	10X32X72
Main Motor Power (KW)	4.0HP/3.0KW
Machine Size (L*W*H) (m)	1.80X0.85X1.15
Approx Weight (Kgs)	1300

For more information, please leave a message, and I can give you detail introduction.

The head machine is a professional cold upsetting forming machine which is matched with automatic wire rolling machine in the whole plant of fastener industry.

Safety instructions

Its purpose is to the selected such as carbon steel, stainless steel, aluminum, copper and other metal wire, with appropriate mould, according to the allowable pressure wire than, under the effect of crankshaft connecting rod drive the slider, automated, fast after the required size of the wire will be automatically shear, extrusion in the mould for needed fastener head type, stem diameter, facilitate thread rolling, or become a qualified rivet type fastener. The heading machine automatically processes, the wire into semi-finished products.

The machine can produce Truss Head, Countersunk Head, Set Screw, Wood Screw, Chipboard Screw, Self Tapping Screw, Flat Head Hex Head, Pan Head, Hexagon Head, Socket Head, Button Head and so on.

SCREW MAKER

One die two blow heading machine. widely used to produce standard and non-standard screw. the machine is easy to operate and stable in performance



Professional ☒
Good quality ☒
Energy conservation ☒

20 YEARS

20 years of professional export

RAINBOW

HIGH-SPEED AUTOMATIC THREAD ROLLING MACHINE



Professional ✓
Good quality ✓
Energy conservation ✓

20 YEARS

20 years of professional export

PRODUCTION AREA

Provide You With A Variety Of Products Meet
The Different Needs Of Customers

