

products Description



a
i
a
m
e
t
e
r
5
c
7
6
w
l
e
n
g
t
h
5
0
r
e
a
d
l
e
n
t
h

7
6
x
8
9
1
2
5
s
s
t
a
t
i
o
n
a
r
y
l
e
n
g
t
h

Details Images

搓丝机参数

/ THREAD ROLLING MACHINE PARAMETERS



CY搓丝机

CY90°Feeding (GEAR IN OUTSIDE) 《CY系列可配合买方尺寸，更改90°牙板》

| 序号 | 机型 | 外径 (mm) | 长度 (mm) | 牙长 (mm) | 牙板 | 马力 (HP) | 产量 (PCS/MIN) | 重量 (KG) | 机台尺寸 (mm) |
|----|-------|---------|-----------------|---------|------------|---------|--------------|---------|----------------|
| 1 | CY05Z | 3-5 | 50/75 | 50 | 76/89/25 | 2.2 | 90-120 | 1000 | 1800×1300×1650 |
| 2 | CY06Z | 3-6 | 50/75 | 75 | 90/105/25 | 4 | 160-185 | 1500 | 1800×1500×1700 |
| 3 | CY10Z | 6-10 | 100/150/200/300 | 100 | 150/165/25 | 11 | 85-120 | 3670 | 2896×1216×2180 |
| 4 | CY12Z | 8-12 | 100/150/200/300 | 100 | 190/215/35 | 15 | 65-85 | 5600 | 3265×1524×2345 |
| 5 | CY16Z | 12-16 | 150/200/300 | 100 | 230/265/38 | 22 | 45-60 | 6700 | 3500×1900×2200 |
| 6 | CY20Z | 14-20 | 200/300 | 150 | 290/330/50 | 30 | 40-50 | 14000 | 2200×4700×2200 |
| 7 | CY24Z | 16-24 | 200/300 | 150 | 380/420/50 | 45 | 35-45 | 18130 | 5100×2320×2600 |
| 8 | CY30Z | 20-30 | 250/300 | 150 | 400/450/50 | 55 | 20-30 | 22330 | 5250×2650×2950 |
| 9 | CY02X | 1-3 | 25 | 20 | 51/64/19 | 0.75 | 275-325 | 830 | 1150×1000×1680 |
| 10 | CY04X | 2-4 | 38 | 32 | 76/89/25 | 1.5 | 230-280 | 1040 | 1560×1180×1790 |
| 11 | CY06X | 3-6 | 50/75 | 50 | 90/105/25 | 4 | 170-200 | 1900 | 2140×1180×2100 |
| 12 | CY08X | 4-8 | 75 | 50 | 108/127/25 | 5.5 | 180-200 | 2215 | 2410×1180×2100 |
| 13 | CY10X | 6-10 | 100/150 | 65 | 150/165/25 | 15 | 130-160 | 4530 | 3100×1640×1970 |
| 14 | CY12X | 8-12 | 100/150 | 75 | 190/215/35 | 22 | 100-140 | 5300 | 3300×1530×1982 |
| 15 | CY16X | 12-16 | 150 | 80 | 230/265/38 | 30 | 75-120 | 7600 | 3720×1800×2620 |
| 16 | CY20X | 14-20 | 150 | 80 | 290/330/50 | 37.5 | 73-85 | 14000 | 3024×1824×2300 |

注：以上技术参数为生产机牙及螺帽D22以下产品的标准，需生产不锈钢等特殊材质产品，建议加大设备规格与本公司业务确认。本公司随时进行研发改进的工作，因此保留随时更改设计、规格尺寸及机械结构之权利，本目录之规格仅供参考。

品质 源于坚守
Quality derives from persistence

信誉 重于泰山
Reputation is weightier than Mount Tai



搓丝机部分结构


/ THREAD ROLLING MACHINE PART OF THE STRUCTURE



斜送送料方式

素材进料与中仁成30°

Transportation Material
Sloping filling-30 degree obliquity with main slider



直送送料方式

素材进料与中仁成90°

Transportation Material
Sloping filling-90 degree obliquity with main slider

RAINBOW

HIGH-SPEED AUTOMATIC THREAD ROLLING MACHINE



- Professional ✓
- Good quality ✓
- Energy conservation ✓

20 YEARS

20 years of professional export



PRODUCT FEATURES

All applications and functions of the thread rolling machine

- ◆ All multi-station models apply air clutch brake with small starting current, allowing operation modes of "Inching", "Single Stroke" and "Continuous Running". The main sliding table can automatically stop at its rear position while operated under "Single Stroke" and "Continuous Running" modes, so as to obtain maximum space for adjustment.



Thread Rolling Machine

**PRODUCT
ADVANTAGES**



Stable, easy to operate, high accuracy, high efficiency, can be full automatic processing thread, straight, textured.