

Product description:

Our thread rolling machine is widely used in domestic China and abroad. It's with high speed, and easy operation.

Technical Parameters:

Model	Diameter (mm)	Screw length (mm)	Thread length(mm)	Moving dies size(mm)	Main Power (Hp)	Output(Pcs/Min)	Approx. wt(KG)
CY05Z	3-5	50/75	50	76/89/25	2.2	90-120	1000
CY06Z	3-6	50/75	75	90/105/25	4	160-185	1500
CY10Z	6-10	100/150/200/300	100	150/165/25	11	85-120	3670
CY12Z	8-12	100/150/200/300	100	190/215/35	15	65-85	5600
CY16Z	12-16	150/200/300	100	230/265/38	22	45-60	6700
CY20Z	14-20	200/300	150	290/330/50	30	40-50	14000
CY24Z	16-24	200/300	150	380/420/50	45	35-45	18130
CY30Z	20-30	250/300	150	400/450/50	55	20-30	22330
CY02X	1-3	25	20	51/64/19	0.75	275-325	830
CY04X	2-4	38	32	76/89/25	1.5	230-280	1040
CY06X	3-6	50/75	50	90/105/25	4	170-200	1900
CY08X	4-8	75	50	108/127/25	5.5	180-200	2215
CY10X	6-10	100/150	65	150/165/25	15	130-160	4530
CY12X	8-12	100/150	75	190/215/35	22	100-140	5300
CY16X	12-16	150	80	230/265/38	30	75-120	7600
CY20X	14-20	150	80	290/330/50	37.5	73-85	14000

Feeding Way:



斜送送料方式

素材进料与中仁成30°

Transportation Material

Sloping filling-30 degree obliquity with main slider



直送送料方式

素材进料与中仁成90°

Transportation Material

Sloping filling-90 degree obliquity with main slider

Machine Packaging:



Exhibition Abroad:

