

A máquina laminadora de rosca adota placa laminadora de rosca com perfil de duas roscas escalonada com design de distância de 1/2 parafuso, uma placa é fixa, a placa móvel está na placa fixa, faz movimento em linha reta para frente e para trás, quando a peça de trabalho é alimentada entre duas placas, placa móvel mova a peça de trabalho para frente, faça sua deformação plástica de superfície em rosca. Para enrolar a rosca na haste vazia do parafuso após a cabeça fria.

RAINBOW

HIGH-SPEED AUTOMATIC THREAD ROLLING MACHINE



Professional ✓
Good quality ✓
Energy conservation ✓

20 YEARS

20 years of professional export

PRODUCT DISPLAY

Various types of thread rolling machine to
meet your various needs



CY06Z



CY08Z



CY10Z



CY12Z



CY16Z



CY30Z



CY02X



CY05X



CY06XN



CY06X



CY08X



CY12X

THREAD ROLLING MACHINE PART OF THE STRUCTURE



TRANSPORTATION MATERIAL

Sloping filling-90 degree obliquity
with main slider



TRANSPORTATION MATERIAL

Sloping filling-30 degree obliquity
with main slider



NO HEAD SCREW

Through no head screw feeding
system, the system solves problems
in no head 'screw bottleneck with
advanced value in machinery.



ORBITAL BRACKET

To stabilize filling progress in order
to avoid floating head and
increases fine quality.



FORCIBLE OIL CARRYING

It replaces traditional acrylic oiler
which damaged main slider. This
precision filter system not only
lowers direct cost in production
but also extends life usage in
recycle.



AUTO FEEDING SYSTEM

Replaced cam by auto feed system,
effectively avoids the cam abrasion
in the production process.