

[illegible]

Auto Multi-Station Cold Forging Fomer

Fomers

□□□□□□□□	DBP-85S	DBP-105S	DBP-135L	DBP-165S	DBP-205S	DBP-225S	DBP-305S
□□□□□□□□□ (□□□)	5	5	5	5	5	5	5
□□□□□□□ (kgs)	80	90	130	220	350	440	550
Dia Cut-Off (□□.)	Ø10	Ø12	Ø16	Ø23	Ø23	Ø30	Ø36
□□□□□□□□□ (□□.)	115	135	190	190	240	253	420
□□□□□□□□□□□□ (PCS/MIN)	90-145	85-130	60-100	55-95	45-75	35-55	25-45
P.K.O Stroke (MM)	25	35	45	45	46	40	60
K.O.Troke (□□.)	92	118	175	178	220	205	380
Main Ram Stroke (mm)	160	190	270	274	346	330	580
□□□□□□□□□□□□□□ (kW)	22	30	37	55	75	110	132
dems.of □□□□□□□□□□□□	Ø50x50l	Ø45x59l	Ø63x69l	Ø75x100l	Ø75x120l	Ø80x130l	Ø118x150l
dems. □□□□□□□□□□□□□□□□	Ø45x125l	Ø53x115l	Ø60x130l	Ø75x185l	Ø90x215L	Ø120x170l	Ø140x300l
dems. □□□□□□□□ Main Die	Ø60x130l	Ø75x135l	Ø86x190l	Ø108x200l	Ø125x240L	Ø140x250l	Ø168x420l
□□□□□□□ (□□.)	80	90	110	129	140	160	180
□□□□□□□□□□□□□□ (t)	17	20	31	52	75	115	200
Applicable Bolt Dia (□□.)	5-8	6-10	8-12.7	10-16	12-20	14-27	24-30
□□□□□□□□□□□□□□□□□□□□ (□□.)	15-90	15-110	20-160	20-160	25-200	35-180	100-350

[illegible]



□□□□□□□□□□□□□□□□□□!