

Technical Specifications

Model	RSH8-90
Number of Stages	8
Flow Rate (m³/h)	90
Flow Rate (GPM)	120
Flow Rate (PCS/MIN)	130
Flow Rate (PCS/MIN)	80-90
Flow Rate (PCS/MIN)	φ60x120
Flow Rate (PCS/MIN) (1st)	φ40x120
Flow Rate (PCS/MIN) (2nd)	φ40x120
Flow Rate (PCS/MIN)	φ28x45
Flow Rate (PCS/MIN)	12x42x90
Power (kW)	10hp/7.5kW
Power (l*w*h) (m)	3.60x1.60x1.80
Weight (kgs)	4800

Additional technical details and notes.

Additional technical details and notes.

Installation and Maintenance

Installation and maintenance instructions.

Additional technical details and notes.



SCREW MAKER

One die two blow heading machine. widely used to produce standard and non-standard screw. the machine is easy to operate and stable in performance



- Professional
- Good quality
- Energy conservation

20 YEARS

20 years of professional export

RAINBOW

HIGH-SPEED AUTOMATIC THREAD ROLLING MACHINE



- Professional ✓
- Good quality ✓
- Energy conservation ✓

20 YEARS

20 years of professional export

PRODUCTION AREA

Provide You With A Variety Of Products Meet
The Different Needs Of Customers

