

Máy cán ren sử dụng hai tấm cán ren định hình ren được thiết kế so le 1/2 khoảng cách vít, Một tấm được cố định, tấm di động nằm trên tấm cố định thực hiện chuyển động thẳng qua lại, khi phôi gia công nạp vào giữa hai tấm, tấm di động di chuyển về phía trước xoắn mảnh phôi, làm cho bề mặt của nó biến dạng dẻo thành ren. Để cuộn ren vào chuôi trống của bu lông sau khi nguội.

RAINBOW

HIGH-SPEED AUTOMATIC THREAD ROLLING MACHINE



Professional

Good quality

Energy conservation

20 YEARS

20 years of professional export

PRODUCT DISPLAY

◆
Various types of thread rolling machine to
meet your various needs



CY06Z



CY08Z



CY10Z



CY12Z



CY16Z



CY30Z



CY02X



CY05X



CY06XN



CY06X



CY08X



CY12X

THREAD ROLLING MACHINE PART OF THE STRUCTURE




TRANSPORTATION MATERIAL

Sloping filling-90 degree obliquity with main slider



TRANSPORTATION MATERIAL

Sloping filling-30 degree obliquity with main slider



NO HEAD SCREW

Through no head screw feeding system, the system solves problems in no head 'screw bottleneck with advanced value in machinery.



ORBITAL BRACKET

To stabilize filling progress in order to avoid floating head and increases fine quality.



FORCIBLE OIL CARRYING

It replaces traditional acrylic oiler which damaged main slider. This precision filter system not only lowers direct cost in production but also extend life usage in recycle.



AUTO FEEDING SYSTEM

Replaced cam by auto feed system, effectively avoids the cam abrasion in the production process.